


Raychem heat-shrinkable medium voltage terminations IXSU-F/OXSU-F for indoor and outdoor applications for polymeric cables up to 42 kV

24 kV



Termination for crimp lug Screened single core plastic and rubber cable

Cross section [mm ²]	Kit number Indoor	Kit number Outdoor	Diameter over insulation HD 620 A2 [mm]
25 - 70	IXSU-F 5121	OXSU-F 5121	17.9 - 23.4
70 - 240	IXSU-F 5131	OXSU-F 5131	21.9 - 32.6
185 - 400	IXSU-F 5141	OXSU-F 5141	27.4 - 37.8
400 - 800	IXSU-F 5151	OXSU-F 5151	35.1 - 46.9
1000 - 1200	IXSU-F 5161	OXSU-F 5161	49.4 - 56.0

Termination with mechanical lug BLMT Screened single core plastic and rubber cable

Cross section [mm ²]	Kit number Indoor	Kit number Outdoor	Diameter over insulation HD 620 A2 [mm]
25 - 95	IXSU-F5121-ML-1-13	OXSU-F5121-ML-1-13	17.9 - 25.0
	IXSU-F5121-ML-1-17	OXSU-F5121-ML-1-17	
95 - 240	IXSU-F5131-ML-4-13	OXSU-F5131-ML-4-13	23.0 - 32.6
	IXSU-F5131-ML-4-17	OXSU-F5131-ML-4-17	
120 - 300	IXSU-F5131-ML-5-13	OXSU-F5131-ML-5-13	24.3 - 34.6
	IXSU-F5131-ML-5-17	OXSU-F5131-ML-5-17	
185 - 400	IXSU-F5141-ML-6-13	OXSU-F5141-ML-6-13	27.4 - 37.8
	IXSU-F5141-ML-6-17	OXSU-F5141-ML-6-17	
	IXSU-F5141-ML-6-21	OXSU-F5141-ML-6-21	
500 - 630	IXSU-F5151-ML-7-17	OXSU-F5151-ML-7-17	37.9 - 44.0
	IXSU-F5151-ML-7-21	OXSU-F5151-ML-7-21	

24 kV



Termination for crimp lug Screened 3-core plastic and rubber cable without armour

Cross section [mm ²]	Tail Length [mm]	Kit number Indoor	Kit number Outdoor
10 - 25	450	IXSU-F 5311	OXSU-F 5311
	1200	IXSU-F 5314	OXSU-F 5314
25 - 50	450	IXSU-F 5321	OXSU-F 5321
	1200	IXSU-F 5324	OXSU-F 5324
70 - 185	450	IXSU-F 5331	OXSU-F 5331
	1200	IXSU-F 5334	OXSU-F 5334
185 - 400	450	IXSU-F 5341	OXSU-F 5341
	1200	IXSU-F 5344	OXSU-F 5344

Termination with mechanical lug BLMT Screened 3-core plastic and rubber cable without armour

Cross section [mm ²]	Tail Length [mm]	Kit number Indoor	Kit number Outdoor
25 - 50	450	IXSU-F5321-ML-1-13	OXSU-F5321-ML-1-13
		IXSU-F5321-ML-1-17	OXSU-F5321-ML-1-17
	1200	IXSU-F5324-ML-1-13	OXSU-F5324-ML-1-13
		IXSU-F5324-ML-1-17	OXSU-F5324-ML-1-17
95 - 185	450	IXSU-F5331-ML-4-13	OXSU-F5331-ML-4-13
		IXSU-F5331-ML-4-17	OXSU-F5331-ML-4-17
	1200	IXSU-F5334-ML-4-13	OXSU-F5334-ML-4-13
		IXSU-F5334-ML-4-17	OXSU-F5334-ML-4-17
185 - 400	450	IXSU-F5341-ML-6-13	OXSU-F5341-ML-6-13
		IXSU-F5341-ML-6-17	OXSU-F5341-ML-6-17
		IXSU-F5341-ML-6-21	OXSU-F5341-ML-6-21
	1200	IXSU-F5344-ML-6-13	OXSU-F5344-ML-6-13
		IXSU-F5344-ML-6-17	OXSU-F5344-ML-6-17
		IXSU-F5344-ML-6-21	OXSU-F5344-ML-6-21