

1.6 - CAJA OVAL. CON TAPA. PARA TUBO RIGIDO E IMC.

1.6 - OVAL CONDUIT BODIES. WITH COVER. FOR USE WITH RIGID AND IMC CONDUIT.

FICHA TECNICA / TECHNICAL DATA

007 - RW - 277

- Material:
 - Cuerpo: Aluminio inyectado a presión (diecast).
 - Tapa: Lámina de Aluminio.
 - Tornillos: Galvanizados.
- Acabados: Pintura electrostática epoxica/poliester polimerizada.
- Rosca NPT para usarse con tubo conduit RIGIDO e IMC.
- Tapa y tornillos ensamblados.
- Empaque: Proporciona hermetismo al agua.
- Fabricación en base a: UL 514 A
CAN/CSA-C22.2 No. 18-92
- Adecuado para áreas clasificadas clase I, división 2 si la instalación cumple con NEC 501-4 (b).

- Material:
 - Body: Diecast aluminum.
 - Cover: Sheet aluminum.
 - Screws: Galvanized steel.
- Finish: Electrostatic powder epoxy/poliester coating.
- NPT threaded for use with RIGID and IMC conduit.
- Cover and screws assembled.
- Gasket: Provide rain tight.
- Manufactured in compliance with: UL 514 A
CAN/CSA-C22.2 No. 18-92
- Suitable for classified location use in class I, division 2 areas if installed in compliance with NEC 501-4 (b).



USAR No. DE CODIGO PARA HACER PEDIDOS / TO ORDER USE CODE NUMBER

| Figura Figure | Catalogo Catalog | Codigo Code | Medida nominal Hub size | | Volumen Volume | | Peso x 100 pzas. Weight x 100 pcs. | | Unit Ctn. Pzas. Pcs. | Ship Ctn. Pzas. Pcs. | Std. Pkg. Pzas. Pcs. | Num. y calib. max. conduct. Max. No. and sze. conduct. |
|------------------|---------------------|----------------|----------------------------|---------|-------------------|--------|---------------------------------------|-------|-------------------------------|-------------------------------|-------------------------------|---|
| | | | mm | inch | cm ³ | cu. in | kg | Lb | | | | |
| | OLB-2986-C | 28.01.2986.C | 12.7 | 1/2 | 65.5 | 4.0 | 11.2 | 24.6 | 10 | 40 | 46 | 3, #8 AWG |
| | OLB-0088-C | 28.01.0088.C | 19.0 | 3/4 | 106.4 | 6.5 | 16.8 | 37.1 | 5 | 35 | 30 | 3, #6 AWG |
| | OLB-0093-C | 28.01.0093.C | 25.4 | 1 | 180.1 | 11.0 | 23.0 | 50.7 | 5 | 20 | 40 | 3, #6 AWG |
| | OLB-0098-C | 28.01.0098.C | 31.8 | 1 1/4 | 512.6 | 31.3 | 52.9 | 116.7 | 2 | 8 | 15 | 3, #2 AWG |
| | OLB-0078-C | 28.01.0078.C | 38.1 | 1 1/2 | 529.0 | 32.3 | 56.4 | 124.4 | 2 | 8 | 15 | 3, #1/0 |
| | OLB-0306-C | 28.01.0306.C | 50.8 | 2 | 1195.7 | 73.0 | 114.8 | 253.1 | 1 | 4 | 6 | 3, #3/0 |
| | OLB-0308-C | 28.01.0308.C | 63.5 S | 2 1/2 S | 1564.2 | 95.5 | 190.0 | 418.8 | 1 | 3 | 4 | 3, #2/0 |
| | OLB-0297-C | 28.01.0297.C | 63.5 L | 2 1/2 L | 2900.0 | 177.0 | 334.0 | 734.8 | 1 | - | 1 | 3, #3/0 |
| | OLB-0310-C | 28.01.0310.C | 76.2 S | 3 S | 1790.3 | 109.3 | 214.9 | 473.9 | 1 | 3 | 4 | 3, #2/0 |
| OLB-0298-C | 28.01.0298.C | 76.2 L | 3 L | 2900.0 | 177.0 | 295.0 | 649.0 | 1 | - | 1 | 3, #3/0 | |
| | OT-2990-C | 28.01.2990.C | 12.7 | 1/2 | 65.5 | 4.0 | 11.5 | 25.3 | 10 | 40 | 42 | 3, #8 AWG |
| | OT-0087-C | 28.01.0087.C | 19.0 | 3/4 | 114.6 | 7.0 | 19.3 | 42.6 | 5 | 40 | 20 | 3, #6 AWG |
| | OT-0092-C | 28.01.0092.C | 25.4 | 1 | 180.1 | 11.0 | 23.0 | 50.76 | 5 | 20 | 32 | 3, #4 AWG |
| | OT-0097-C | 28.01.0097.C | 31.8 | 1 1/4 | 496.3 | 30.3 | 52.9 | 116.7 | 2 | 8 | 15 | 3, #2 AWG |
| | OT-0077-C | 28.01.0077.C | 38.1 | 1 1/2 | 512.6 | 31.3 | 65.9 | 145.4 | 2 | 8 | 15 | 3, #2 AWG |
| | OT-0307-C | 28.01.0307.C | 50.8 | 2 | 1126.9 | 68.8 | 108.8 | 240.0 | 1 | 4 | 6 | 3, #1 AWG |
| | OT-0309-C | 28.01.0309.C | 63.5 S | 2 1/2 S | 1528.2 | 93.3 | 186.4 | 411.1 | 1 | 3 | 4 | 3, #1 AWG |
| | OT-0301-C | 28.01.0301.C | 63.5 L | 2 1/2 L | 2800.9 | 170.9 | 353.0 | 776.6 | 1 | - | 1 | 3, #2/0 |
| | OT-0311-C | 28.01.0311.C | 76.2 S | 3 S | 1765.7 | 107.8 | 235.4 | 519.1 | 1 | 3 | 4 | 3, #1 AWG |
| OT-0302-C | 28.01.0302.C | 76.2 L | 3 L | 2800.9 | 170.9 | 294.5 | 647.9 | 1 | - | 1 | 3, #2/0 | |
| | OC-2989-C | 28.01.2989.C | 12.7 | 1/2 | 65.5 | 4.0 | 10.2 | 22.4 | 10 | 70 | 63 | 3, #8 AWG |
| | OC-0330-C | 28.01.0330.C | 19.0 | 3/4 | 119.5 | 7.3 | 15.8 | 34.9 | 5 | 50 | 36 | 3, #6 AWG |
| | OC-0331-C | 28.01.0331.C | 25.4 | 1 | 185.0 | 11.3 | 21.5 | 47.4 | 5 | 20 | 46 | 3, #4 AWG |
| | OC-2625-C | 28.01.2625.C | 31.8 | 1 1/4 | 455.9 | 27.8 | 51.5 | 113.4 | 2 | 8 | 16 | 3, #2 AWG |
| | OC-2626-C | 28.01.2626.C | 38.1 | 1 1/2 | 488.7 | 29.8 | 57.0 | 125.5 | 2 | 8 | 16 | 3, #2 AWG |
| | OC-2627-C | 28.01.2627.C | 50.8 | 2 | 1087.3 | 66.3 | 104.5 | 230.0 | 1 | 4 | 9 | 3, #2/0 |

Especificaciones sujetas a cambio sin previo aviso. Specifications are subject to change without notice.