

2.1 - CAJA OVAL "S". CON TORNILLO. CON TAPA. PARA TUBO EMT (THINWALL).


Hoja: 2 / 3
Page:

2.1 - OVAL CONDUIT BODIES "S". SETSCREW. WITH COVER. FOR USE WITH EMT CONDUIT.

FICHA TECNICA / TECHNICAL DATA

007-RW-152

USAR No. DE CODIGO PARA HACER PEDIDOS / TO ORDER USE CODE NUMBER

Figura Figure	Catalogo Catalog	Codigo Code	Medida nominal Hub size		Volumen Volume		Peso x 100 pzas. Weight x 100 pcs.		Unit Ctn. Pzas. Pcs.	Ship Ctn. Pzas. Pcs.	Std. Pkg. Pzas. Pcs.	Num. y calib. max. conduct. Max. No. and sze. conduct.
			mm	inch	cm ³	cu. in	kg	Lb				
	* OLR-3477-TC	28.11.3477.TC	12.7 S	1/2 S	65.5	4.0	14.3	31.5	10	40	52	3, #8 AWG
	* OLR-0090-TC	28.11.0685.TC	19.0	3/4	119.5	7.3	16.8	37.1	5	40	24	3, #6 AWG
	OLR-0095-TC	28.11.0686.TC	25.4	1	185.0	11.3	23.0	50.7	5	20	40	3, #4 AWG
	OLR-0100-TC	28.11.0687.TC	31.8	1 1/4	512.6	31.3	52.4	115.6	2	8	15	3, #2 AWG
	OLR-0080-TC	28.11.0688.TC	38.1	1 1/2	540.5	33.0	56.9	125.5	2	8	15	3, #1/0
	OLR-0320-TC	28.11.0689.TC	50.8	2	1203.9	73.5	124.8	275.2	1	4	6	3, #4/0


*Certificaciones / Compliances:  Expediente/File No. LR 105795-3

TAPAS


COVERS

- Lámina de aluminio troquelada.
- Tornillos galvanizados incluidos

- Sheet aluminum.
- Galvanized screws included.





USAR No. DE CODIGO PARA HACER PEDIDOS / TO ORDER USE CODE NUMBER

Figura Figure	Catalogo Catalog	Codigo Code	Medida nominal Hub size		Espesor Thickness		Peso x 100 pzas. Weight x 100 pcs.		Pqt. Unit Pzas. Pcs.	Unit Ctn. Pzas. Pcs.	Ship Ctn. Pzas. Pcs.	Std Pkg. Pzas. Pcs.
			mm	inch	mm	inch	kg	Lb				
	TO-2991	28.02.2991	12.7 S	1/2 S	1.7	.067	1.8	3.9	10	60	600	1500
	TO-0356	28.02.0356	19.0	3/4	1.7	.067	2.0	4.4	10	60	600	1500
	TO-0357	28.02.0357	25.4	1	1.7	.067	2.7	5.9	10	40	400	1000
	TO-0363	28.02.0363	31.8	1 1/4	1.7	.067	5.0	11.0	10	20	200	500
	TO-0363	28.02.0363	38.1	1 1/2	1.7	.067	5.0	11.0	10	20	200	500
	TO-0373	28.02.0373	50.8	2	1.7	.067	8.5	18.7	10	40	160	300

TORNILLOS CAUTIVOS DE ACERO INOXIDABLE (Opcional) / CAPTIVE STAINLESS STEEL SCREWS (Optional)
Se surten en bolsa aparte Supplied separately

USAR No. DE CODIGO PARA HACER PEDIDOS / TO ORDER USE CODE NUMBER

Figura Figure	Descripción Description	Codigo Code	Medida / Size		Largo/Length mm	inch
	TORNILLO CAUTIVO INOXIDABLE	52.05.0196.IX	TOR. # 8 - 32 NC		9.52	3/8
	CAPTIVE STAINLESS STEEL SCREW	52.05.0216.IX	TOR. # 12 - 24 NC		9.52	3/8
		52.05.0198.IX	TOR. 7.9 - 18 NC		15.87	5/8
	TORNILLO CAB. FILLISTER	52.05.0041.Z	TOR. # 8 - 32 NC		9.52	3/8
	FILLISTER SCREW	52.05.0040.Z	TOR. 4.76 - 24 NC		9.52	3/8

Certificaciones: / Compliances:  Expediente No. LR 105795 - 3
File No.

Especificaciones sujetas a cambio sin previo aviso. Specifications are subject to change without notice.

RAWELT, S.A. de C.V.

 RAWELT® INYECTADOS

Una División del Grupo REVUELTA 

25 - V - 2009