



BURNDY Catalog Number Q2A344N
 UPC Number 781810322208
 Description 400-500 CU 2 COND 4 HO
 Status Active

Web Use
 BURNDY Product Line

Dimensional	
Length (in)	4.69
Thickness (in)	3/8
Height (in)	2
D or Diameter (Fraction) (in)	3-1/8
Hole Size (Fraction)	9/16
Stud Size (in)	1/2
Thickness	0.38
D - in	3.13
Pad Width (in)	3
N (Fraction)	5/8
E - in	1.75
N (in)	0.63
Hole Size (in)	0.56
Length (Fraction)	4-11/16
Height (Fraction) (in)	2
General	
Number of Holes	4
Product Description	Copper Terminal, 4 Hole, 400-500 kcmil, 1/2" Stud, 1-3/4" Stud Hole Spacing, 2 Screws
Conductor(s)	
Copper Solid Size (Range)	N/A
Navy Cable Size (Range)	N/A
Copper Stranded (Range)	400 kcmil-500 kcmil
Physical	
Installation Torque	375
Type of Plating	Unplated
Connector Type	Terminal
Plated (Yes or No)	N
Product Material	Copper
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	N
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B