



BURNDY Catalog Number YGL29C29
 UPC Number 781810220023
 Description 2-250 TO 2-250 GRD GRID/
 Status Active

Web Use
 BURNDY Product Line

Dimensional	
Length (in)	2.50
B Length (in)	0.75
BB - Length (in)	.75
General	
Product Description	Copper Compression Cross Grid Connector, 2 AWG (Str)-250 kcmil or 1/2"-5/8" Rod or #3-4 Rebar, 2 AWG (Str)-250 kcmil
Prefilled (Oxide Inhibitor)	Y
Other	
Type of Oxide Inhibitor	Penetrox E
Approvals / Certifications	
Rated for Direct Burial	Y
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467,IEEE 837
Conductor(s)	
Rod Size (Side A) - Range	1/2 in-5/8 in
Rod Size (Side B) - Range	N/A
Rebar Size (Side B) - Range	N/A
Copper Solid Size (Side A) - Range	N/A
Copper Str Size(Side B) - Range	2 AWG-250 kcmil
Copper Str Size (Side A) - Range	2 AWG-250 kcmil
CopperSolid Size (Side B) - Range	N/A
Rebar Size (Side A) - Range	3 -4
Physical	
Type of Plating	Unplated
Plated (Yes or No)	N
Index Number	997
Product Material	Copper
Documentation	